



AFLLED2

ForceLINE LED 156W



Features

Powerful and robust IP65 low/high bay, perfect for the demands of industrial applications

Mounting brackets supplied as standard for dropprod or chain/wire installation

Comparable to 4 x 55W PL

Powered by Philips

Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan

Anti-glare polycarbonate diffuser maximises performance and light output

LED lifespan L70 51,000 hours

General Information

Lamp Type	LED
IP Rating	IP65
IK Rating	IK09
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	600
Width (mm)	239
Height (mm)	109

Technical Information

Wattage	156W
Lumens Delivered	15474lm
Lm/W	99lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 50°C

Technical Data - ETIM - High bay luminaire (EC001716)

Mounting method	Pendant
With light source	Yes
Suitable for number of lamps	1
Material housing	Aluminium
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Light distributor	Diffuser lens/optic/panel
Degree of protection (IP)	IP65
Impact strength	IK09
Protection class	I
Max. system power	156 W
Rated luminous flux acc. IEC 62722-2-1	15474 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Width	239 mm
Height/depth	109 mm
Length	600 mm
Suitable for emergency lighting	No

Datasheet generated from <https://onetimepim.com> last updated Tuesday, December 1, 2020 9:49:25 AM

