



ATASLED/WL

Talana Solar LED - Cool White



Features

Ultra modern die-cast solar powered aluminium LED wall light

PIR motion sensor as standard

2 operation modes:-1) 11% output after sunset, motion detected 100% output, no motion 11% for 20 hours 2) Motion detected 100% output, no motion off

Graphite textured powder coat paint finish

LED lifespan L70 36,000 hours

General Information

Lamp Type	LED
Colour / Finish	Graphite
IP Rating	IP54
Class Protection	3
Internal / External	External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Width (mm)	210
Height (mm)	170
Depth (mm)	245
Accessories	ASBP/17

Technical Information

Lumens Delivered	210lm
CRI	Ra 80
CCT	4000K
Operating Temp	-20°C to 45°C

Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
With light source	Yes
Material housing	Aluminium
Colour housing	Other
Control gear included	Yes
Degree of protection (IP)	IP54
Protection class	III
Suitable for emergency lighting	No
With movement sensor	Yes
Rated luminous flux acc. IEC 62722-2-1	210 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Width	210 mm
Height/depth	245 mm
Length	170 mm

Datasheet generated from <https://onetimepim.com> last updated Thursday, August 6, 2020 9:19:14 AM

