



ATORLED4/M3

Tornado IP65 LED Non-Corrosive - Self Test Emergency 20W Grey



Features

LED Performance allows point-to-point replacement of existing fluorescent luminaires.

Light output exceeds performance of T8 and T5 fluorescent.

Unique luminaire fixing clip design allows option of mounting onto BESA box.

Lockable heavy-duty stainless steel clips supplied as standard for added safety and security.

LED lifespan L70 30,000 hours.

Self-test emergency as standard.

General Information

Lamp Type	LED
Colour / Finish	Grey
Emergency	Yes
Self Test	Yes
IP Rating	IP65
IK Rating	IK07
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface/Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1266
Width (mm)	85
Height (mm)	75

Technical Information

Wattage	20W
Lumens Delivered	2088lm
Lm/W	104lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 40°C

Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP65
Impact strength	IK07
Protection class	I
Suitable for emergency lighting	Yes
With movement sensor	No
With light sensor	No
Max. system power	20 W
Rated luminous flux acc. IEC 62722-2-1	2088 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Luminaire efficacy	104 lm/W
Width	85 mm
Height/depth	75 mm
Length	1266 mm

Datasheet generated from <https://onetimepim.com> last updated Monday, May 11, 2020 12:48:42 PM

	Code	A	B	C	D
	ATORLED4	1266	860	75	85
	ATORLED5	1566	960	75	85
	ATORLED6	1866	1030	80	85
	ATORLED2X4	1266	860	75	118
	ATORLED2X5	1566	960	75	118
	ATORLED2X6	1855	1030	80	118