



AERMLED3/60/CW/DD



Features

- Backlit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Low glare and even light distribution for multiple applications
- TPa as standard
- Surface mounting frame option
- Powered by Tridonic

General Information

Lamp Type	LED
Colour / Finish	White
Dimmable	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Recessed/Suspended
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 50,000
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	10
Accessories	AERMLD/SK, AERMLD/60/SMF, AERMLD/60/CGCB/KIT, APRK/60

Technical Information

Wattage	32W
Lumens Delivered	3330lm
Lm/W	104lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50-60Hz
Operating Temp	-20°C to 40°C
SDCM	6
UGR	17

Datasheet generated from <https://onetimepim.com> last updated Monday, June 6, 2022 12:10:49 PM



