



AGDLED



Features

Shallow 2-In-1 LED direct / indirect recessed luminaire with outstanding efficiency characteristics.

Each fitting supplied with chrome central louvre and high transmission diffuser options (high gloss black or white central louvres available as optional accessories).

Up to 70% saving compared to 2x55W PL-L.

Quick access termination point for rapid installation.

Instant light output and unlimited switching.

Small unobtrusive microwave sensor option.

LED lifespan L70 56,000 hours.

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Height (mm)	53
Accessories	AGDLED/WLA, AGDLED/BLA, AIRMLED/PRK

Technical Information

Wattage	37W
Lumens Delivered	3300lm
Lm/W	89lm
CRI	Ra 80
CCT	4000k
Input	230V
Hertz	50Hz
Operating Temp	0°C to 25°C

Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
With light source	Yes
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP20
Protection class	I
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Max. system power	37 W
Rated luminous flux acc. IEC 62722-2-1	3300 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Luminaire efficacy	89 lm/W
Width	595 mm
Height/depth	53 mm
Length	595 mm

Datasheet generated from <https://onetimepim.com> last updated Tuesday, December 1, 2020 9:51:27 AM

