



## ALOTLED



### Features

High performance indirect recessed luminaire

UGR<19 (unified glare rating) compliant luminaire ideal for most interior lighting applications

Ideal for office or commercial applications

Selectable CCT between 3000K, 4000K and 6000K output

Exceeds performance of 2x40W PL-L

Powder coated steel construction

LED lifespan L70 30,000 hours

TP(a) as Standard

## General Information

Lamp Type	LED
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Diffuser Rating	TP(a)
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Height (mm)	80

## Technical Information

Wattage	29W
Lumens Delivered	3051lm (Warm White), 3178lm (Cool White), 3178lm (Daylight)
Lm/W	105lm (Warm White), 110lm (Cool White), 110lm (Daylight)
CRI	Ra 80
CCT	3000/4000/6000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C

## Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
With light source	Yes
Material housing	Steel
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP20
Protection class	II
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Max. system power	29 W
Colour of light	White
Colour temperature	3000-6000 K
Colour rendering index CRI	80-89
Width	595 mm
Height/depth	80 mm
Length	595 mm

Datasheet generated from <https://onetimepim.com> last updated Tuesday, December 1, 2020 9:51:24 AM

