



## ASPELED/60/CCT



### Features

High performance minimalist LED panel frame for commercial and architectural applications

Hollow illuminated frame allows installation of standard ceiling panel to sit inside frame and level with grid

Integral switch allows the installer a choice of 3000K, 4000K and 6500K colour temperature options

LED lifespan L70 50,000 hours

## General Information

Lamp Type	LED
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	14

## Technical Information

Wattage	28W
Lumens Delivered	2995lm (Cool White), 2877lm (Warm White), 3000lm (Daylight)
Lm/W	111lm (Cool White), 103lm (Warm White), 103lm (Daylight)
CRI	Ra 80
CCT	3000/4000/6500K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C

## Technical Data - ETIM - Ceiling-/wall luminaire (EC002892)

Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	No
With light source	Yes
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Degree of protection (IP)	IP20
Protection class	II
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Max. system power	28 W
Colour of light	White
Colour temperature	3000-6500 K
Colour rendering index CRI	80-89
Height/depth	14 mm
Length	595 mm

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 2:32:40 PM

