AZPLLED/3/M3

Features

Powerful and durable IP65 linear high bay, perfect for the demands of industrial applications

1.5m suspension kit supplied as standard

4 x stainless steel rawl bolts supplied as standard for surface installation

A number of installation options available with suspended and surface mounting options provided as standard

AZPLLLED/3 exceeds performance of 4x80W T5

Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan

Plug and play microwave sensor option, offering maximum energy saving

LED Lifespan L80 B10 54,000 hours

0/1-10V dimmable as standard (installer must drill through pilot hole and use an IP rated gland on install)

General Information

Lamp Type	LED
Emergency	Yes
IP Rating	IP65
IK Rating	IK10
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface/Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1122
Width (mm)	147
Height (mm)	134
Accessories	AZPLLED/MWS, AZPLLED/LC, AZPLLED/MWSP

Technical Information

Wattage	200W
Lumens Delivered	27850lm
Lm/W	140lm
CRI	Ra 80
CCT	5000K
Input	230V
Hertz	50/60Hz
Operating Temp	-30°C to 40°C

Datasheet generated from https://onetimepim.com last updated Tuesday, April 20, 2021 2:14:27 PM


1122


119
134
147