

---

## ENPO2QA/B4K1670-SS0

ENPO2QA; Post Top Offset Mount, 2 Quadrant Adjacent, Black, Clear Diffuser, 16 LED, 700mA, Symmetrical LED Orientation, S0 Optic

---



### Range Information

A New Modular, Architectural Street Lighting Collection  
IK10

### Range Specification

- UK designed, developed and manufactured.
- 100,000 hours (L90, F10).
- Tool free maintenance.
- IP66 protection using bespoke poured gaskets.
- IK10+ impact resistance, marine grade, LM6 aluminium and polycarbonate body.
- 1000+ hours salt spray using environmentally friendly Metavate pre-treatment.

### Range Options

- 60 - 76mm Post top mounting.
- Offset post top mounting and suspension options.
- Customisable quadrant blanking available.
- Mini Cell option available.
- PIR option available
- NEMA Socket option available.
- Clear and opal diffusers available.
- Black - ENPC2QA/B

### Technical Information

|                     |        |
|---------------------|--------|
| <b>Colour</b>       | Black  |
| <b>Diffuser</b>     | Clear  |
| <b>CCT</b>          | 4000 K |
| <b>System Power</b> | 36W    |

|                         |           |
|-------------------------|-----------|
| <b>Delivered Lumens</b> | 3630lm    |
| <b>Efficacy</b>         | 100.8lm/W |
| <b>Size</b>             |           |
| <b>Diameter</b>         | 670mm     |
| <b>Height 1</b>         | 96mm      |
| <b>Height 2</b>         | 170mm     |

