

---

## ENPO2QA/B4K2450-SS0

ENPO2QA; Post Top Offset Mount, 2 Quadrant Adjacent, Black, Clear Diffuser, 24 LED, 500mA, Symmetrical LED Orientation, S0 Optic

---



### Range Information

A New Modular, Architectural Street Lighting Collection  
IK10

### Range Specification

- UK designed, developed and manufactured.
- 100,000 hours (L90, F10).
- Tool free maintenance.
- IP66 protection using bespoke poured gaskets.
- IK10+ impact resistance, marine grade, LM6 aluminium and polycarbonate body.
- 1000+ hours salt spray using environmentally friendly Metavate pre-treatment.

### Range Options

- 60 - 76mm Post top mounting.
- Offset post top mounting and suspension options.
- Customisable quadrant blanking available.
- Mini Cell option available.
- PIR option available
- NEMA Socket option available.
- Clear and opal diffusers available.
- Black - ENPC2QA/B

### Technical Information

<b>Colour</b>	Black
<b>Diffuser</b>	Clear
<b>CCT</b>	4000 K
<b>System Power</b>	37.9W

---

<b>Delivered Lumens</b>	4134lm
<b>Efficacy</b>	109lm/W
<b>Size</b>	
<b>Diameter</b>	670mm
<b>Height 2</b>	170mm
<b>Height 1</b>	96mm

